## **DECLARATION OF PERFORMANCE**

Nro. 079-FF-2015-04-14

- 1. **Unique identification code of the product-type:** Extruded polystyrene (XPS) Finnfoam FK-29 240mm.
- 2. Allowing identification of the construction product: EAN-Code: 64 18711 59240 2
- 3. **Intended uses of the construction product:** Products are used as thermal insulation. Product applications are specified in the web site <u>www.finnfoam.fi</u>.
- 4. Name, registered trade name and contact address of the manufacturer:

Finnfoam Oy (0689386-6) Satamakatu 5 24100 Salo, Finland Tel. +358 2 777 300 Fax: +358 2 777 3020 Email: finnfoam@finnfoam.fi

- 6. System of attestation of conformity: AVCP 3
- 7. Declaration of performance concerning a construction product covered by a harmonized standard:

VTT Expert Services (NB. 0809) and Institute of thermal insulation of Vilnius Gediminas Technical University (NB. 1688) performed initial type testing under system 3 and issued test/calculation reports.



## 9. Declared performance:

| Essential characteristics                        | Performance | Harmonized technical specification |
|--|-------------|------------------------------------|
| Reaction to fire                                 | F           | EN 13164:2012                      |
| Long term water absorption<br>by total immersion | NPD         |                                    |
| Long term water absorption<br>by diffusion       | NPD         |                                    |
| Release of dangerous<br>substances               | No releases |                                    |
| Thermal resistance RD<br>(m <sup>2</sup> K)/W    | 7,75        |                                    |
| Thermal conductivity λο<br>W/(mK)                | 0,031       |                                    |
| Thickness  | T1          |                                    |
| Water vapour transmission                        | NPD         |                                    |
| Compressive strength                             | NPD         |                                    |
| Tensile strength                                 | NPD         |                                    |
| Dimensional stability                            | DS(23,90)   |                                    |
| Freeze-thaw resistance                           | NPD         |                                    |
| Compressive creep                                | NPD         |                                    |

## Safety data sheet: www.finnfoam.fi/kayttoturvallisuustiedote

Signed for and on behalf of the manufacturer by:

Henri Nieminen, CEO

Salo 14.4.2015

(signature)

